

DS-D5AC11T7-16S5 OPS Module



- Intel® Iris® Xe Graphics, support 4K resolution
- Support M.2 nvme system disk quick start
- Support 3 USB 3.0 ports, 3 USB2.0 ports, 1 HDMI port, 1 DP interface, 1 Type-C port
- Support dual channel memory
- Support Wi-Fi IEEE 802.11 a/b/g/n/ac

▪ Specification

Built-in System	
Operation System	WIN10 SAC
Processor	Intel® Core, i7 11th
CPU Clock Speed	2.8GHz
Memory	8G * 2
NIC	Integrated 10/100/1000M Adaption
Graphics	Intel® Iris® Xe Graphics
Platform Architecture	Intel® Tiger Lake
Storage	512G
Cooling System	Single Brass & Single Fan
Interface	
Network Interface	RJ45 * 1
Data Transmission Interface	Bluetooth 4.2 USB 3.0 * 3; USB 2.0 * 3; Type-C * 1
Video Output	HDMI * 1; DP * 1
Antenna	2
Power	
Standby Consumption	0.5W
Input Voltage	12V-19V DC
Max. Consumption	95W
Working Environment	
Working Temperature	0°C - 40°C
Working Humidity	10%-90%
Storage Temperature	-20°C - 60°C
Storage Humidity	10%-90%
General	
Product Dimensions (W × H × D)	195×30×180mm
Package Dimensions (W × H × D)	Carton with a single module : 308 * 80 * 278 mm Carton with five modules : 420 * 298 * 320 mm
Net Weight	About 1.22kg
Gross Weight	Carton with a single module : about 1.36 kg Carton with five modules : about 7.50 kg
Color	Black

▪ Available Model

DS-D5AC11T7-16S5

▪ **Accessory**

▪ **Optional**

DS-D5B86RB/C	DS-D5B75RB/C	DS-D5B86RB/D	DS-D5B65RB/D	DS-D5B75RB/D
				
DS-D5B65RB/C				
				

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8907-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

